


TCP-C-SI is a thermally conductive silicone cap for an optimised thermal coupling between electronic packages and heat sinks which provides for a reliable electrical all-around insulation. Through the specific formulation and filling with thermally conductive ceramic particles a good thermal conductivity is reached. Its conformal surface structure guarantees a very good compliance to the contact surfaces. Thus the total thermal resistance is minimised.



Release 09 / 2026

PROPERTIES

- ☐ Very good surface compliance
- ☐ High thermal contact
- ☐ Extraordinary chemical resistance and longterm stability
- ☐ Residue-free removal after use

AVAILABILITY

- ☐ Thicknesses: 0.5 mm and 0.8 mm
- ☐ Different sizes available

APPLICATION EXAMPLES

Thermal link of:


- ☐ MOSFETs or IGBTs
 - ☐ Power diodes or AC/DC converters
- For use in Switch mode power supplies / Motor control units / Automotive engine management systems / UPS units / Solar systems

Technical Data Sheet

PROPERTY	UNIT	TCP-C250-SI	TCP-C280-SI
MATERIAL		Ceramic filled silicone	Ceramic filled silicone
Colour		Grey	Grey
Thickness	mm	0.50	0.80
Tensile Strength ¹	kpsi	0.5	0.5
Tear Strength	kN/m	6.0	6.0
UL Flammability	UL 94	V0	V0
RoHS Conformity	2015 / 863 / EU	Yes	Yes
THERMAL			
Resistance @ 30 PSI	°C·inch ² /W	0.48	0.58
Thermal Conductivity	W/mK	1.0	1.0
Operating Temperature Range	°C	- 40 to + 155	- 40 to + 155
ELECTRICAL			
Breakdown Voltage ²	kV AC	4	10
Volume Resistivity	Ohm · cm	2.6 x 10 ¹⁵	2.6 x 10 ¹⁵
Dielectric Constant	@ 1 MHz	4.85	4.85

Measurement technique according to: ¹ ASTM D 412, ² ASTM D 149. Typical, non-binding values. Not intended for specification purposes. Subject to technical changes. Please contact us for further information.

SIZES IN MM	A	B	C	D
TCP-C150-SI	16.0 ± 0.8	11.5 ± 0.5	5.9 ± 0.3	0.5 ^{+0.15} _{-0.05}
TCP-C250-SI	21.5 ± 0.8	11.5 ± 0.5	5.9 ± 0.3	0.5 ^{+0.15} _{-0.05}
TCP-C280-SI	21.8 ± 0.8	12.1 ± 0.5	6.5 ± 0.3	0.8 ^{+0.15} _{-0.05}
TCP-C450-SI	28.5 ± 0.8	17.5 ± 0.5	5.9 ± 0.3	0.5 ^{+0.15} _{-0.05}
TCP-C480-SI	28.8 ± 0.8	18.2 ± 0.5	6.6 ± 0.3	0.8 ^{+0.15} _{-0.05}



All technical data and information are without warranty and believed to be reliable and accurate, corresponding to the latest state of the art. Since the products are not provided to conform with mutually agreed specifications and their use and processing are unknown we cannot guarantee results, freedom from patent infringement, or their suitability for any application. Product testing by the applicant is recommended. We reserve the right of changes.